

BASIC RESEARCH IN PLASMA-ENHANCED CPMBUSTION

4 November 2009

Dr Julian Tishkoff
Program Manager
AFOSR/NA
Air Force Research Laboratory

maintaining the data needed, and cor including suggestions for reducing the	ction of information is estimated to av- mpleting and reviewing the collection his burden, to Washington Headquarter d be aware that notwithstanding any of MB control number.	of information. Send comments regars Services, Directorate for Informat	rding this burden estimate or a ion Operations and Reports, 12	ny other aspect of this 15 Jefferson Davis Hi	collection of information, ghway, Suite 1204, Arlington	
1. REPORT DATE 04 NOV 2009	2. REPORT TYPE	3. DATES COVERED 00-00-2009 to 00-00-2009				
4. TITLE AND SUBTITLE				5a. CONTRACT NUMBER		
Basic Research in Plasma-Enhanced Cpmbustion				5b. GRANT NUMBER		
				5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S)				5d. PROJECT NUMBER		
				5e. TASK NUMBER		
				5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Air Force Research Laboratory, AFOSR/NA, Arlington, VA, 22203				8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)		
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)		
12. DISTRIBUTION/AVAILA Approved for public	ABILITY STATEMENT C release; distribution	ı unlimited				
13. SUPPLEMENTARY NOT	ES					
14. ABSTRACT						
15. SUBJECT TERMS						
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE	
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified	Same as Report (SAR)	13	PERSON	


Report Documentation Page

Form Approved OMB No. 0704-0188





RUSSIAN AJAX HYPERSONIC FLIGHT VEHICLE (1994)



TECHNICAL CHALLENGES


- Uniform Plasma Generation
- Power Required; System Impact
- High Re, Q Environment
- Measurement/Modeling


PAYOFFS

- Drag Reduction
- Thermal Management
- Flight Control
- Size, Weight reduction
- Few Moving Parts
- Power generation
- Ignition/Combustion Enhancement











THEME OBJECTIVE: Understand, Predict, And Control Weakly Ionized Flows To Revolutionize The Performance Of Aerospace Vehicles









RESEARCH

- Aerodynamic Drag Reduction
- MHD Flow Control
- Glow Discharge Flow Control
- Plasma Generation
- Ignition / Combustion
 Enhancement

AFOSR PROGRAM MANAGER TEAM


Bob Barker
Mike Berman
Fariba Fahroo
Arje Nachman
Julian Tishkoff
John Schmisseur








U.S. RESEARCH AFOSR PLASMA THEME











RUSSIAN/UKRAINIAN RESEARCH









Time



2009 MULTIDISCIPLINARY UNIVERSITY RESEARCH INITIATIVE

CHEMICAL ENERGY ENHANCEMENT BY NONEQUILIBRIUM PLASMA SPECIES

The Legacy



PLASMA IGNITION




PLASMA IGNITION ALTERNATIVES



Glow Discharge (Adamovich/Ohio State)

dV/dt = 0



Streamer Discharge (Gundersen/USC)

 $dV/dt > 1 kV/\mu s$



Nanosecond Discharge (Starikovskii/MIPT)

dV/dt > 1 kV/ns




PLASMA IGNITION



SHOCK TUBE EXPERIMENTS DEMONSTRATE IGNITION DELAY REDUCTION BY FAST IONIZATION WAVES

Results Validate Previous Model Predictions



- Nanosecond Corona Discharge at 0.2 MPa Pressure And By Volume Nanosecond Discharge At 0.05 MPa Pressure
- Ignition Not Possible Without Fast Ionization Wave At 0.05 MPa Pressure




PLASMA IGNITION



PLASMA STREAMER DISCHARGES MODELED

Provides Initialization For Calculations Of Plasma-Enhanced Combustion



Plasma Streamer Discharge Image

- Modeling Based On Solving Transport Equations For Primary And Secondary Electrons
- Experimental Validation Through Measurements Of Electric Field Strength For Streamer Discharges In Oxygen-Nitrogen Gas Mixtures

Excitation Chemistry

$$N_2^+ \to N_4^+$$
 (0.1 ns)

$$N_4^+ \to O_2^+$$
 (1 ns)

$$O_2^+ \to O_4^+$$
 (5 ns)


$$e^- \to O_2^-$$
 (70 ns)

Starikovskii/MIPT



100% INCREASE IN DIFFUSION FLAME QUENCH VELOCITY GRADIENT REALIZED WITH GLIDING ARC DISCHARGE

Means To Stabilize Combustion In Scramjets



- Gliding Discharge Initiated By Helical Inner Electrode And Stabilized Near The Quenching Limit By Field From A 0.15 Tesla Magnet, Producing 20-50 Hz Rotation
- Plasma-Based Thermal Addition Found To Be Negligible, Implying Non-Thermal Plasma Stabilization



COMBUSTION AND DIAGNOSTICS



